
MULE™ 4010 TRANS4x4®









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Fuel Capacity 6.3 gal
Turning Radius 12.8 ft
Cargo Bed 50.4 x 4

Cargo Bed 50.4 x 47.6 x 11.2 in (2-person), 30.3 x 47.6 x 11.2 in (4person)

800 lb (2-person), 401 lb (4-person)

(LxWxH)

Cargo Bed Load

Rear Brakes

Capacity

Drum

Payload Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 75.8 in

Curb Weight 1587.6 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

