## **MULE PRO-DX™ EPS DIESEL**







| D | N | ١ | A  | E | D |
|---|---|---|----|---|---|
| Г | u | ľ | N. | Г | π |

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2400 rpm

Bore x Stroke 2.91x3.03 in

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output 55 amp

(max)

Ground Clearance 10.4 in

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

**Fuel Capacity** 

Payload Capacity

Seating Capacity

----i--- C-----it--

Towing Capacity 2000 lb

**Lighting** (2) Halogen headlights.

7.9 gal

1581 lb

54.1 x 53.7 x 11.0 in

## **CAPABILITY**

Front Suspension / Wheel Travel

wheet mavet

Rear Suspension / Wheel Travel

Double wishbone/8.7 in

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 26x9.00-12

**Rear Tires** 26x11.00-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

**Front Brakes** 

Independent, Mechanical Disc

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1852.2 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Wheel Type Stee

Color Choices Timberline Green

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

