MULE PRO-DXT™ EPS DIESEL







POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2400 rpm

Bore x Stroke 2.91x3.03 in

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 55 amp

CAPABILITY

Wheel Travel

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12 **Rear Tires** 26x11.00-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.2 in **Fuel Capacity** 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

Cargo Bed Load

Capacity

999 lb (3-person), 350 lb (6-person)

Payload Capacity 1581 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1936.0 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip

meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Steel **Wheel Type**

Color Choices Timberline Green

Warranty Kawasaki 3-Year Limited Warranty



