





Single 220mm petal disc with dual-piston

Single 184mm petal disc with single-piston

90/100-14

caliper

caliper

165.3 lb*

1.32 gal

49.8 in

Lime Green

Not Available

D	N	V	M	C	D
Г	U	ľ	V	C	П

2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression 10.9:1 (low speed) - 9.0:1 (high speed)

Ratio

Fuel System 28mm Keihin carburetor

Ignition CDI with digital advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Curb Weight

Fuel Capacity

Color Choices

Wheelbase

Warranty

Rear Tire

Front Brakes

Rear Brakes

Frame Type	High-tensile steel perimeter design with subframe member
Rake/Trail	29°/3.8 in
Overall Length	72.0 in
Overall Width	30.1 in
Overall Height	43.3 in
Ground Clearance	11.4 in
Seat Height	32.7 in

PERFORMANCE

Suspension / with 20-way co

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire 70/100-17



