2024 KLX®140R L







Rear Tire 90/100-16 POWER **Front Brakes** Single 220mm petal disc with a dualpiston caliper Engine 4-stroke single, SOHC, air-cooled **Rear Brakes** Single 186mm petal disc with single-Displacement 144cc piston caliper **Bore x Stroke** 58.0 x 54.4mm DETAILS Compression 9.5:1 Ratio High-tensile steel, box-section perimeter Frame Type 20mm Keihin carburetor **Fuel System** Rake/Trail 27°/3.8 in Ignition Digital DC-CDI **Overall Length** 74.6 in 5-speed, return shift, with wet multi-disc Transmission manual clutch **Overall Width** 31.1 in **Final Drive** Chain **Overall Height** 42.3 in Ground 10.0 in PERFORMANCE Clearance **Seat Height** 31.5 in 33mm telescopic fork/7.1 in Front Suspension / **Curb Weight** 209.4 lb* Wheel Travel **Fuel Capacity** 1.5 gal Uni-Trak[®] linkage system and single shock Rear with piggyback reservoir, fully adjustable Suspension / Wheelbase 50.6 in Wheel Travel preload and 22-way rebound damping/7.1 in **Color Choices**

Front Tire

Scan with camera

to view videos.

key features

and more.

70/100-19

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.

Warranty

Lime Green, Battle Gray

6 Month Limited Warranty