KLX®230 S









POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

9.4:1

Compression

Ratio

Maximum Torque 13.2 lb-ft @ 6,400 rpm

DFI® with 32mm throttle body

Fuel System
Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider

Aids

Seated Cham

Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel 37mm telescopic fork/7.8 in

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

Front Tire

2.75 x 21

Rear Tire

4.10 x 18

Front Brakes

Single 240mm (265mm ABS Model) petal disc

with a dual-piston caliper (and ABS)

Rear Brakes

Single 220mm petal disc with single-piston

caliper (and ABS)

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.6°/3.7 in

Overall Length 81.8 in

Overall Width 33.2 in

Overall Height 44.8 in

Ground 9.4 in

Clearance

Curb Weight

33.2 in

Seat Height 33.2 in

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices

Lime Green, Battle Gray

Warranty

12 Month Limited Warranty

291.0/293.2 lb* 50-State Model



