## **KX**<sup>™</sup>450X







D	N	V	V	С	D
Г	U	V	V	C	π

4-stroke single, DOHC, liquid-cooled **Engine** 

Displacement 449cc

**Bore x Stroke** 96.0 x 62.1mm

12.5:1

Compression

**Fuel System** 

**Ratio** 

Ignition

DFI® with 44mm Keihin throttle body

Modes

**Transmission** 5-speed, return shift, with wet multi-disc manual

clutch and hydraulic clutch actuation

Digital CDI with handlebar-controlled Power

**Final Drive** Chain

**Electronic Rider** 

Aids

Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode

## **PERFORMANCE**

**Front Suspension** / Wheel Travel

49mm inverted telescopic coil-spring fork with 21way adjustable compression and 22-way adjustable rebound damping/12.0 in

**Rear Suspension** / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in

**Front Tire** 80/100-21

**Rear Tire** 120/80-18

**Front Brakes** Single semi-floating 270mm Braking/Sunstar

petal disc with Brembo master cylinder and dual-

piston caliper

Single 240mm Braking/Sunstar petal disc with **Rear Brakes** 

single-piston caliper

## **DETAILS**

**Frame Type** Aluminum perimeter

Rake/Trail 27.0°/4.6 in

**Overall Length** 85.6 in

**Overall Width** 32.1 in

**Overall Height** 49.6 in

**Ground Clearance** 13.2 in

**Seat Height** 37.4 in

**Curb Weight** 239.8 lb\* without fuel / 249.9 lb\*

**Fuel Capacity** 1.64 gal

Wheelbase 58.3 in

**Special Features** Smartphone Connectivity via RIDEOLOGY THE APP

**Color Choices** Lime Green

Warranty Not Available



