MULE[™] 4010 4x4 FE







POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99 x 2.68 in

Compression Ratio

Fuel System

Transmission

Final Drive

(max)

DFI® with 34mm Mikuni throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

23 amp

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires

23x11.00-10

Rear Tires 23x11.00-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Independent, Mechanical Drum

Front Brakes

Drum

Rear Brakes

Drum

Ground Clearance 6.9 in

Turning Radius 11.2 ft

Cargo Bed 46.3 x 51.6 x 11.4 in

6.3 gal

Dimensions (LxWxH)

Fuel Capacity

Cargo Bed Load 800 lb

Capacity

Payload Capacity 1,312 lb

Seating Capacity

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, horn, 12V DC outlet, fuel gauge, hour

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

