## 2024 NINJA<sup>®</sup> 7 HYBRID ABS





METALLIC BRIGHT SILVER/METALLIC MATTE LIME GREEN/ EBONY



## **POWER**

	Engine	4-stroke, Parallel Twin, DOHC, liquid-cooled	Rear Su Wheel
	Displacement	451cc	Front T
	Bore x Stroke	70.0 x 58.6mm	Rear Ti
	<b>Compression Ratio</b>	11.7:1	Front B
	Maximum System Torque	44.2 lb-ft @ 2,800 rpm	Rear Br
	Fuel System	EFI with dual 36mm throttle bodies	DET
	Ignition	тсві	
	Traction Motor	Liquid-cooled, interior permanent magnet	Rake &
		synchronous motor	Overall
	Power Modes	3 Modes (SPORT-HYBRID/ ECO-HYBRID/EV) plus e- boost	Overall
	Motor Drive	48 V lithium-ion battery	Overall
	Battery Type		Ground
	Transmission	6-speed Automated Manual	Seat He
	Shifter Mechanism	Push button	Curb W
	Final Drive Ratio	3.071 (14/43)	Fuel Ca
	Final Drive	Chain	Wheelb
	Electronic Rider Aids	Automatic Launch Position Finder (ALPF) in MT, WALK Mode (with Reverse), Anti-lock Brake System (ABS)	Special
PERFORMANCE			Color C

Front Suspension/ Wheel Travel	41mm telescopic fork/4.7 in
Rear Suspension/ Wheel Travel	Bottom-Link Uni-Trak® with single gas-charged shock, adjustable spring preload/4.5 in
Front Tire	120/70-17
Rear Tire	160/60-17
Front Brakes	Dual 300mm discs with 2-piston calipers and ABS
Rear Brakes	Single 220mm disc with single-piston caliper and ABS

## DETAILS

	Rake & Trail	25°/4.1 in
	Overall Length	84.4 in
	Overall Width	29.5 in
	Overall Height	44.7 in
	Ground Clearance	5.1 in
	Seat Height	31.3 in
	Curb Weight	502.7 lb* (incl. battery)
	Fuel Capacity	3.7 gal
	Wheelbase	60.4 in
<	Special Features	e-boost, Idling Stop Function, Regenerative System, TFT Color Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP
	Color Choices	Metallic Bright Silver/Metallic Matte Lime Green/ Ebony
	Warranty	12 Month Limited Warranty



Frame Type

Trellis, high-tensile steel

\*Curb weight includes all necessary materials, fluids, and batteries to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Visit peru.kawasaki-la.com for full product details.