2024 NINJA H2[®] ABS





MIRROR COATED SPARK BLACK



POWER

| Engine | Liquid-cooled, 4-stroke, In-Line Four, DOHC, 16- valve |
|--------------------------|--|
| Displacement | 998cc |
| Bore x Stroke | 76.0 x 55.0mm |
| Compression Ratio | 8.5:1 |
| Maximum Torque | 104.9 lb-ft @ 11,000 rpm |
| Fuel System | DFI® with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger |
| Ignition | Digital |
| Transmission | 6-speed, return, dog-ring |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper |
| | |

| Front Tire | 120/70 ZR17 (58W) |
|--------------|--|
| Rear Tire | 200/55 ZR17 (78W) |
| Front Brakes | Dual radial-mount, opposed 4-piston Brembo Stylema® calipers, dual semi-floating 330mm discs, Kawasaki Intelligent anti-lock Brake System (KIBS) |
| Rear Brakes | Opposed 2-piston calipers, single 250mm disc, Kawasaki Intelligent anti-lock Brake System (KIBS) |

DETAILS

| Frame Type | Trellis, high-tensile steel, with swingarm mounting plate |
|------------------|--|
| Rake/Trail | 24.5°/4.1 in |
| Overall Length | 82.1 in |
| Overall Width | 30.3 in |
| Overall Height | 44.3 in |
| Ground Clearance | 5.1 in |
| Seat Height | 32.5 in |
| Curb Weight | 524.8 lb* |
| Fuel Capacity | 4.5 gal |
| Wheelbase | 57.3 in |
| Special Features | Smartphone Connectivity via RIDEOLOGY THE APP, all-LED lighting, Highly Durable Paint, TFT Instrumentation |
| Color Choices | Mirror Coated Spark Black |
| Warranty | 12 Month Limited Warranty |
| | |

PERFORMANCE

| Front Suspension / Wheel Travel | 43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in |
|------------------------------------|---|
| Rear Suspension / Wheel Travel | Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and top-out spring/5.3 in |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.