


2024

NINJA H2[®]R ABS

Kawasaki
Let the Good Times Roll[®]



 MIRROR COATED MATTE SPARK BLACK



POWER

| | |
|------------------------------|---|
| Engine | Liquid-cooled, 4-stroke, In-Line Four, DOHC, 16-valve |
| Displacement | 998cc |
| Bore x Stroke | 76.0 x 55.0mm |
| Compression Ratio | 8.3:1 |
| Maximum Torque | 121.5 lb-ft @ 12,500 rpm |
| Fuel System | DFI [®] with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger |
| Ignition | Digital |
| Transmission | 6-speed, return, dog-ring |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Kawasaki Cornering Management Function (KCMF), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper |

| | |
|---------------------|--|
| Front Tire | 120/60 ZR17 V01F slick |
| Rear Tire | 190/65 ZR17 V01R slick |
| Front Brakes | Dual radial-mount, opposed 4-piston Brembo Stylema [®] calipers, dual semi-floating 330mm discs, Kawasaki Intelligent anti-lock Brake System (KIBS) |
| Rear Brakes | Opposed 2-piston calipers, single 250mm disc, Kawasaki Intelligent anti-lock Brake System (KIBS) |

DETAILS

| | |
|-------------------------|---|
| Frame Type | Trellis, high-tensile steel, with swingarm mounting plate |
| Rake/Trail | 25.1° / 4.3 in |
| Overall Length | 81.5 in |
| Overall Width | 33.5 in |
| Overall Height | 45.7 in |
| Ground Clearance | 5.1 in |
| Seat Height | 32.7 in |
| Curb Weight | 476.3 lb* |
| Fuel Capacity | 4.5 gal |
| Wheelbase | 57.1 in |
| Special Features | Aerodynamic downforce generating devices, Highly Durable Paint, Analog Tach & LCD instrumentation |
| Color Choices | Mirror Coated Matte Spark Black |
| Warranty | N/A |

PERFORMANCE

| | |
|--|---|
| Front Suspension / Wheel Travel | 43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in |
| Rear Suspension / Wheel Travel | Uni-Trak [®] , Öhlins TTX36 gas charged shock with piggyback reservoir, 30-way compression and rebound damping adjustability, 16-way spring preload adjustability, and top-out spring/5.3 in |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.