## NINJA® ZX™-6R 40th ANNIVERSARY EDITION ABS









D	n	17	M	C	D
Г	u	T.	٧	C	π

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-

cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression

Ratio

12.9:1

Fuel System DFI® with 38mm Keihin throttle bodies (4) and

oval sub-throttles

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

**Electronic Rider** 

Aids

Kawasaki TRaction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS)

(upshift only)

## **PERFORMANCE**

Front Suspension / Wheel Travel

41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs /4.7 in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully

adjustable spring preload/5.9 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes

Dual semi-floating 310mm discs with dual radial-mounted, monobloc, opposed 4-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 220mm petal discs with single-piston

caliper, Kawasaki Intelligent anti-lock Brake

System (KIBS)

## **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 23.5°/4.0 in

Overall Length 79.7 in

Overall Width 28.0 in

Overall Height 43.3 in

**Ground Clearance** 5.1 in

Seat Height 32.7 in

Curb Weight 436.6 lb\*

Fuel Capacity 4.5 gal

Wheelbase 55.1 in

**Special Features** 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green/Pearl Crystal White/Blue

**Warranty** 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

