RIDGE® LIMITED HVAC







12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,499/1,100 lb CA Model

3, bench seat

All-LED lighting

2.500 lb



POWER

4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 92.0 hp1 @ 8,500 rpm **Maximum Torque** 65.8 lb-ft @ 5.500 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1

FFI **Fuel System**

Ignition TCBI with Digital Advance

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 4WD with locking rear differential, shaft

Engine Braking Yes

Alternator Output

(max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator

Duro 27 x 9-14

DETAILS

Lighting

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel Frame

Overall Length 128.9 in **Overall Width** 64.0 in **Overall Height** 81.1 in

Dry Weight 2,022.0/2,024.2 lb** CA Model **Curb Weight** 2.127.8/2.130.0 lb* CA Model

Wheelbase 90.7 in

Instruments

Warranty

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding

Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)

Additional Features 8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab

with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR^{TM} system compatible

Color Choices Metallic Shadow Gold

Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Rear Suspension /

Wheel Travel

Front Tires

Rear Tires

Wheel Type

Steering

Front Brakes

Rear Brakes

Ground Clearance

Duro 27 x 11-14 14" Aluminum

> Rack-and-pinion w/ Electric Power Steering (EPS) Dual hydraulic 249mm discs with two-piston calipers

Dual hydraulic 249mm discs with single-piston calipers

12.6/13.6 in (max preload); 12.6 in CA Model

Long-Travel, Double Wishbone/12.7 in

Long-Travel, Double Wishbone/12.7 in

Scan with camera to view videos, key features and more.

