

2024

RIDGE® RANCH EDITION



METALLIC STARDUST WHITE



POWER		DETAILS	
Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled	Fuel Capacity	12.9 gal
Displacement	999cc	Turning Radius	15.0 ft
Maximum Horsepower	92.0 hp¹ @ 8,500 rpm	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Maximum Torque	65.8 lb-ft @ 5,500 rpm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Bore x Stroke	73.4 x 59.0mm	Payload Capacity	1,499/1,100 lb CA Model
Compression Ratio	10.6:1	Seating Capacity	3, bench seat
Fuel System	EFI	Towing Capacity	2,500 lb
Ignition	TCBI with Digital Advance	Lighting	All-LED lighting
Starting System	Electric		
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)		
Final Drive	Selectable 4WD with locking rear differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	126.4 in
Alternator Output (max)	85 amp	Overall Width	64.0 in
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Overall Height	81.9 in
		Dry Weight	1,808.1/1,810.3 lb** CA Model
		Curb Weight	1,909.5/1,911.7 lb* CA Model
		Wheelbase	90.7 in
		Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
		Additional Features	WARN® VRX 45 Powersport Winch, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible
		Color Choices	Metallic Stardust White
		Warranty	Kawasaki STRONG 3-Year Limited Warranty
CAPABILITY			
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		
Front Tires	Duro 27 x 9-14		
Rear Tires	Duro 27 x 11-14		
Wheel Type	14" Aluminum		
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		
Ground Clearance	12.6/13.6 in (max preload); 12.6 in CA Model		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit peru.kawasaki-la.com for full product details.