RIDGE® XR HVAC









12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1.000/600 lb CA Model

1,499/1,100 lb CA Model

2, bucket seat

All-LED lighting

2.500 lb

POWER

4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 116.0 hp1 @ 8,500 rpm **Maximum Torque** 73.8 lb-ft @ 8.000 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1 **Fuel System**

Ignition TCBI with Digital Advance

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R) **Final Drive** Selectable 4WD with locking front/rear differential, shaft

Engine Braking Yes

Alternator Output (max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator

DETAILS

Lighting

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel Frame

Overall Length 125.4 in **Overall Width** 64.0 in **Overall Height** 82.3 in

Estimated Dry Weight 1,960.3/1,962.5 lb** CA Model **Curb Weight** 2.066.1/2.068.3 lb* CA Model

Wheelbase 90.7 in

Instruments

Warranty

Digital speedometer, tachometer, fuel gauge, odometer, dual trip

meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil

pressure, water temperature)

Additional Features Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®,

Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system

compatible

Color Choices Ice Gray, Metallic Graystone

Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Rear Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Front Tires **Rear Tires**

Duro 30 x 10-14 Duro 30 x 10-14

Wheel Type

14" Aluminum

Steering **Front Brakes** Rack-and-pinion w/ Electric Power Steering (EPS) Dual hydraulic 249mm discs with two-piston calipers

Rear Brakes

Dual hydraulic 249mm discs with single-piston calipers

Ground Clearance

13.8/14.6 in (max preload); 13.8 in CA Model

Scan with camera to view videos, key features and more.

