2024 TERYX4™









POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with two 36mm Mikuni throttle bodies

TCBI with Electronic Advance Ignition

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential,

shaft

Engine Braking Yes **Ground Clearance** 11.2 in

Fuel Capacity 7.9 gal **Turning Radius** 16.7 ft

Cargo Bed Dimensions (LxWxH)

17.9 x 47.6 x 8.7 in

Cargo Bed Load

Capacity

249 lb

Payload Capacity 1,109 lb

Seating Capacity

Towing Capacity 1,300 lb

Lighting (2) incandescent headlights, (2) LED taillights, LED

stoplight

CAPABILITY

Double Wishbone; FOX Podium coil-over shocks with Front Suspension / **Wheel Travel** piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in

Rear Suspension / Double Wishbone; FOX Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way **Wheel Travel**

compression damping/8.3 in

Front Tires Maxxis® 26 x 9-12

Rear Tires Maxxis® 26 x 11-12

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Steel Tube Double-X Reinforcement **Frame**

Overall Length 125.4 in **Overall Width** 60.0 in

Overall Height 77.8 in

Curb Weight 1,605.2 lb* / 1,607.4 lb* CA Model

Wheelbase 85.6 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter

and parking-brake indicator, R/N/P/4WD, water temp

and low-oil-pressure indicators

Color Choices Metallic Moondust White/Super Black

Kawasaki Strong 3-Year Limited Warranty Warranty



