2024 **VULCAN[®] S**







120/70x18

160/60/17

POWER

		Rear Tire	160/60x17
Engine Displacement	4-stroke, 2-cylinder, DOHC, liquid-cooled 649cc	Front Brakes	Single 300mm disc with twin-piston caliper, (and ABS)
Bore x Stroke	83.0 x 60.0mm	Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)
Compression Ratio Maximum	10.8:1 46.3 lb-ft @ 6,600 rpm	DETAILS	
Torque		Frame Type	High-tensile steel diamond frame
Fuel System	DFI® with 38mm throttle bodies (2), with sub- throttle valves	Rake/Trail	31°/4.7 in
Ignition	TCBI with Electronic Advance	Overall Length	90.9 in
Transmission	6-speed with positive neutral finder	Overall Width	34.6 in
Final Drive	Sealed chain	Overall Height	43.3 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Ground Clearance	5.1 in
		Seat Height	27.8 in
PERFORMANCE		Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)

Front Tire

PERFURMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	Fuel Capacity Wheelbase	3.7 gal 62.0 in
Rear Suspension /	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	Color Choices	Pearl Sand Khaki/Ebony, Metallic Flat Spark Black
Wheel Travel		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.