



2025

# BRUTE FORCE® 300

**Kawasaki**  
Let the Good Times Roll®



-  GRAYISH BLUE
-  TIMBERLINE GREEN



## POWER

|                   |  |
|-------------------|--|
| Engine            | 4-stroke, single-cylinder, SOHC, liquid-cooled                                       |
| Displacement      | 271cc  |
| Bore x Stroke     | 72.7 x 65.2mm  |
| Compression Ratio | 11.0:1   |
| Maximum Torque    | 15.9 lb-ft @ 6,500 rpm   |
| Fuel System       | Keihin CVK32 carburetor  |
| Ignition          | DC-CDI   |
| Transmission      | Automatic Continuously Variable Transmission (CVT) with centrifugal clutch (H,L,N,R) |
| Final Drive       | 2WD, shaft   |

|                                 |   |
|---------------------------------|---|
| Steering                        | Conventional tie-rod                                |
| Electronic Power Steering (EPS) | No  |
| Turning Radius                  | 9.2 ft  |
| Towing Capacity                 | 500 lb  |
| Total Rack Capacity             | 110 lb  |
| Rack Capacity, Front/Rear       | 44/66 lb  |
| Lighting                        | (2) 35W headlights, 5W taillight, and 21W stoplight |

## CAPABILITY

|                                 |                                    |
|---------------------------------|------------------------------------|
| Front Suspension / Wheel Travel | Independent double wishbone/5.2 in |
| Rear Suspension / Wheel Travel  | Swingarm with single shock/5.6 in  |
| Front Tires                     | AT 22 x 7-10 Maxxis® tubeless      |
| Rear Tires                      | AT 22 x 10-10 Maxxis® tubeless     |
| Front Brakes                    | Dual 148mm discs                   |
| Rear Brakes                     | Single 148mm disc                  |
| Ground Clearance                | 6.1 in                             |
| Starting System                 | Electric                           |
| Fuel Capacity                   | 3.2 gal                            |

## DETAILS

|                  |  |
|------------------|--|
| Frame Type       | Double-cradle, steel   |
| Tread Width      | 33.5/32.7 in   |
| Track Front/Rear | 33.5/32.7 in   |
| Overall Length   | 75.4 in  |
| Overall Width    | 42.5 in  |
| Overall Height   | 46.1 in  |
| Seat Height      | 33.3 in  |
| Curb Weight      | 535.8 lb*  |
| Wheelbase        | 45.9 in  |
| Instruments      | Speedometer, odometer, clock, fuel gauge, and coolant temp light |
| Color Choices    | Grayish Blue, Timberline Green                                   |
| Warranty         | 12 Month Limited Warranty  |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to [www.atvsafety.org](http://www.atvsafety.org). ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [peru.kawasaki-la.com](http://peru.kawasaki-la.com) for full product details.