ELEKTRODE® 20









P	N	V	N	F	R

Air-cooled, brushless, in-wheel **Motor Type Power Modes** 3 modes (High / Mid / Low) Max Speed by Mode -24 mph / 24 mph / 13 mph H/M/L

Battery Type Lithium-ion (in-frame) Battery Voltage/ 50.4 V 10.2 Ah (514.1 Wh) Capacity

Battery Charge Time 4 hours (approx)*

Drive System Direct hub motor, chainless

Battery Rated Output 750 W

Battery Running Time Low: 180 minutes / High: 60 minutes

Maximum Battery Charge Cycles

500 (after which 80% of original charge capacity)

PERFORMANCE

Frame Type **Aluminum**

Front Suspension/ 28mm telescopic fork / 50mm **Wheel Travel**

Rear Suspension/ 28mm telescopic fork / 50mm Wheel Travel

Front Tire 20 x 2.125 **Rear Tire** 20 x 2.125

Front Brakes 160mm mechanical disc 160mm mechanical disc **Rear Brakes**

Handlebar Clamp Size 22.2mm **Steering Stem Size** 28.6mm **Seat Post Size**

27.2mm

DETAILS

Rake & Trail 25 deg / 2.95 in (75mm)

Overall Length 59.3 in (1,505mm) **Overall Width** 26.3 in (668mm) 36.6 in (929mm) **Overall Height**

Ground Clearance 7.1 in (181mm)

Seat Height 21.6-27.3 in (550-693mm)

38.93 in (989mm) Wheelbase **Curb Weight** 46.1 lb (20.9 kg) **Color Choices** Lime Green, Black

Appropriate Rider's

source

Rider Weight (max) 132 lb (60 kg)

Yes (rotating pedal, foldable) **Footrest**

Charging power 110-V AC (Home)

Charging connector

Front of bike **Number plate** STD, MX-Style

WARRANTY

Frame and Fork TBA Non-Electrical TBA Components TBA

Electric System Components

Normal Wear and Tear Items

TBA

Scan with camera to view videos, key features and more.

