ELEKTRODE® 20FS







-	_				_
Р	Ш	ľ	N	E	ĸ
					•

Air-cooled, brushless, in-wheel **Motor Type Power Modes** 3 modes (High / Mid / Low) Max Speed by Mode -24 mph / 24 mph / 13 mph

H/M/L

Battery Type Lithium-ion (in-frame) 50.4 V 10.2 Ah (514.1 Wh)

Battery Voltage/ Capacity

Drive System

Battery Charge Time 4 hours (approx)* Direct hub motor

Battery Rated Output

750 W

Battery Running Time

Low: 180 minutes / High: 60 minutes

Maximum Battery Charge Cycles

500 (after which 80% of original charge capacity)

PERFORMANCE

Aluminum Frame Type

Front Suspension/ **Wheel Travel**

Steel fork / rigid

Rear Suspension/ Wheel Travel

Rigid

Front Tire 20 x 1.95 **Rear Tire** 20 x 1.95

Front Brakes 160mm mechanical disc 160mm mechanical disc **Rear Brakes**

Handlebar Clamp Size Steering Stem Size

22.2mm 28.6mm **Seat Post Size**

27.2mm

DETAILS

Rake & Trail 25 deg / 2.95 in (75mm)

Overall Length 59.2 in (1,504mm) **Overall Width** 28.2 in (716mm)

38.9 in (989mm) **Overall Height Ground Clearance** 6.7 in (171mm)

Seat Height 23.3-29.6 in (593-751mm)

38.97 in (990mm) Wheelbase **Curb Weight** 46.1 lb (20.9 kg) **Color Choices** Flat Metallic Gray

Appropriate Rider's

Rider Weight (max) 176 lb (80 kg)

Yes (rotating pedal, foldable) **Footrest**

Charging power source

110-V AC (Home)

Charging connector

Front of bike

Number plate STD, BMX-Style

WARRANTY

Frame and Fork TBA Non-Electrical TBA Components

Electric System Components

TBA

Normal Wear and Tear Items

TBA

Scan with camera to view videos, key features and more.

