²⁰²⁵ KFX®50







Conventional tie-rod

No

8.9 ft

N/A

N/A

N/A

N/A

POWER

Engine	4-stroke, single-cylinder, air-cooled	
Displacement	49.5cc	
Bore x Stroke	39.0 x 41.4mm	
Compression Ratio	10.8:1	
Maximum Torque	N/A	
Fuel System	Keihin PTE16 carburetor	
Ignition	Solid state CDI	
Transmission	Automatic Continuously Variable Transmission (CVT)	
Final Drive	2WD, chain	

CAPABILITY

Fro Wh Re Wh Fro Re Fro Re Gro Sta

		Track Front/Rear	27.2/27.
ront Suspension / /heel Travel	Single A-arm with twin shocks/2.8 in	Overall Length	55.1 in
ear Suspension /	Swingarm with single shock/2.9 in	Overall Width	34.1 in
Iheel Travel		Overall Height	34.8 in
ront Tires	AT 16 x 8-7 tubeless	Seat Height	25.0 in
ear Tires	AT 16 x 8-7 tubeless	Curb Weight	249.2 lb
ront Brakes	Dual mechanical drums	Wheelbase	38.0 in
ear Brakes	Hydraulic disc	Instruments	N/A
round Clearance	3.3 in	Color Choices	Lime Gi
tarting System	Electric with back-up kick-starter	Warranty	12 Mont
uel Capacity	1.4 gal		





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki's KFX®50 is recommended for use only by persons 6 or older, and the KFX®90 is recommended for use only by persons 10 and older. All children under 16 riding ATVs should always have direct adult supervision. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, org o to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.

DETAILS

Steering

Electronic Power

Towing Capacity

Rack Capacity,

Front/Rear

Lighting

Total Rack Capacity

Steering (EPS) Turning Radius

Frame Type	Double-cradle, steel
Tread Width	27.2/27.6 in
Track Front/Rear	27.2/27.6 in
Overall Length	55.1 in
Overall Width	34.1 in
Overall Height	34.8 in
Seat Height	25.0 in
Curb Weight	249.2 lb*
Wheelbase	38.0 in
Instruments	N/A
Color Choices	Lime Green, Battle Gray
Warranty	12 Month Limited Warranty