²⁰²⁵ **KLX®140R**







POWER		Rear Tire	90/100-14
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Front Brakes	Single 220mm petal disc with a dual- piston caliper
Displacement	144cc	Rear Brakes	Single 186mm petal disc with single- piston caliper
Bore x Stroke	58.0 x 54.4mm		
Compression Ratio	9.5:1	DETAILS	
Fuel System	Keihin PB20 carburetor	Frame Type	High-tensile steel, box-section perimeter
Ignition	Digital DC-CDI	Rake/Trail	27.0°/3.3 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Length	71.7 in
		Overall Width	31.1 in
Final Drive	Chain	Overall Height	41.3 in
PERFORMANCE		Ground Clearance	9.3 in
Front	33mm telescopic fork/7.1 in	Seat Height	30.7 in
Suspension / Wheel Travel		Curb Weight	205.0 lb*
Rear	Uni-Trak® linkage system and single shock	Fuel Capacity	1.5 gal
Suspension / Wheel Travel	with 5-way preload adjustability/7.1 in	Wheelbase	49.6 in
Front Tire	70/100-17	Color Choices	Lime Green, Battle Gray
		Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.