²⁰²⁵ **KLX[®]230R S**







POWER		Rear Tire	100/100-18
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Front Brakes	Single 240mm petal disc with a dual- piston caliper
Displacement	233cc	Rear Brakes	Single 220mm petal disc with single- piston caliper
Bore x Stroke	67.0 x 66.0mm		
Compression Ratio	9.4:1	DETAILS	
Fuel System	DFI® with 32mm Keihin throttle body	Frame Type	High-tensile steel, box-section perimeter
Ignition	TCBI with electronic advance	Rake/Trail	24.6°/3.9 in
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Length	80.5 in
		Overall Width	33.3 in
Final Drive	Chain	Overall Height	46.7 in
PERFORMANCE		Ground Clearance	10.6 in
Front Suspension / Wheel Travel	37mm telescopic fork/8.7 in	Seat Height	34.4 in
		Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
Rear	Uni-Trak [®] linkage system and single shock	Fuel Capacity	1.7 gal
Suspension / Wheel Travel	with adjustable spring preload/8.8 in	Wheelbase	53.3 in
Front Tire	80/100-21	Color Choices	Lime Green, Battle Gray
		Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.