## KLX®230SM ABS







**BATTLE GRAY** 

D	n	١	M	Г	D
Г	U	ľ	N	E	π

**Engine** 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Maximum Torque 13.0 lb-ft @ 6,400 rpm

Fuel System DFI® with 32mm throttle body

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider Anti-lock Brake System (ABS)

Aids

**Front Brakes** 

Single 300mm petal disc with a dual-piston

caliper and ABS

**Rear Brakes** 

Single 220mm petal disc with single-piston

caliper and ABS

## **DETAILS**

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.9°/3.0 in

Overall Length 80.1 in

Overall Width 33.3 in

Overall Height 44.3 in

**Ground Clearance** 

8.7 in

Seat Height 33.1 in

**Estimated Dry** 

Weight

284.4/286.5 lb\*\* 50-State Model

Curb Weight 299.9/302.1 lb\* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

**Color Choices** Battle Gray

**Warranty** 12 Month Limited Warranty

## **PERFORMANCE**

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire 110/70-17

Rear Tire 120/70-17



