

2025

KLX[®]300R



- LIME GREEN
- BATTLE GRAY



POWER

| | |
|-------------------|---|
| Engine | 4-stroke, single-cylinder, DOHC, liquid-cooled |
| Displacement | 292cc |
| Bore x Stroke | 78.0 x 61.2mm |
| Compression Ratio | 11.0:1 |
| Fuel System | DFI [®] with 34mm Keihin throttle body |
| Ignition | TCBI with electronic advance |
| Transmission | 6-speed, return shift with wet multi-disc manual clutch |
| Final Drive | Chain |

PERFORMANCE

| | |
|---------------------------------|--|
| Front Suspension / Wheel Travel | 43mm inverted telescopic fork with adjustable compression damping/11.2 in |
| Rear Suspension / Wheel Travel | Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/11.2 in |
| Front Tire | 3.0 x 21 |

| | |
|--------------|--|
| Rear Tire | 4.6 x 18 |
| Front Brakes | Single 270mm petal disc with a dual-piston caliper |
| Rear Brakes | Single 240mm petal disc with single-piston caliper |

DETAILS

| | |
|------------------|--------------------------------------|
| Frame Type | Semi-double cradle |
| Rake/Trail | 26.9° / 4.3 in |
| Overall Length | 86.6 in |
| Overall Width | 32.5 in |
| Overall Height | 49.0 in |
| Ground Clearance | 11.8 in |
| Seat Height | 35.4 in |
| Curb Weight | 282.2 lb* / 286.7 lb* 50-State Model |
| Fuel Capacity | 2.1 gal |
| Wheelbase | 56.5 in |
| Color Choices | Lime Green, Battle Gray |
| Warranty | 6 Month Limited Warranty |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.