MULE[™] 4010 4x4 FE









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 23 amp

(max)

Front Suspension / **Wheel Travel**

CAPABILITY

MacPherson Strut/3.9 in

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires 23 x 11-10 **Rear Tires** 23 x 11-10

Rack-and-pinion w/ Electric Power Steering (EPS) Steering

Park Brake Type

Independent, mechanical drum

Front Brakes Drum **Rear Brakes** Drum **Ground Clearance** 6.9 in

Fuel Capacity 6.3 gal **Turning Radius** 11.2 ft

46.3 x 51.6 x 11.4 in

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load Capacity

1,312 lb **Payload Capacity**

Seating Capacity

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



