## **MULE PRO-DX™ EPS**









## **POWER**

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 5

(max)

55 amp

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

**Rear Tires** 

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12

Steering Electric Power Steering (EPS), Tilt steering

26 x 11-12

Park Brake Type Independent, mechanical disc

Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

ton caliper Warranty

Ground Clearance 10.4 in

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

**Payload Capacity** 

**Fuel Capacity** 

Capacity

999 lb 1,574 lb

7.9 gal

54.1 x 53.7 x 11.0 in

Seating Capacity 3-person

eating capacity 5-perso

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

**Estimated Dry** 

Weight

1,781.6 lb\*\*

Curb Weight 1,858.8 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Color Choices Bright White

Varranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.