## **MULE PRO-DX™ EPS**









## **POWER**

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 55 amp

(max)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

**Ground Clearance** 

....

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity

999 lb

54.1 x 53.7 x 11.0 in

10.4 in

Payload Capacity 1,574 lb

Seating Capacity 3-person

Towing Capacity 2,000 lb

**Lighting** (2) Halogen headlights

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires

26 x 9-12

Rear Tires

26 x 11-12

Steering

Electric Power Steering (EPS), Tilt steering

**Park Brake Type** 

Independent, mechanical disc

**Front Brakes** 

Dual disc, 2-piston caliper

**Rear Brakes** 

Dual disc, 1-piston caliper

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

**Estimated Dry** 

1,781.6 lb\*\*

Weight
Curb Weight

1,858.8 lb\*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

**Color Choices** 

**Bright White** 

Warranty

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULEIM PRO Series side stide's Rollover Protective Structure (ROS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.