

2025

MULE PRO-MX™ LE



DEEP BLUE



POWER

|                         |   |
|-------------------------|---|
| Engine                  | 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled                       |
| Displacement            | 695cc   |
| Maximum Torque          | 42.7 lb-ft @ 5,000 rpm  |
| Bore x Stroke           | 102.0 x 85.0mm  |
| Compression Ratio       | 10.3:1  |
| Fuel System             | DFI® with 44mm throttle body  |
| Transmission            | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)   |
| Final Drive             | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking          | Yes   |
| Alternator Output (max) | 35.7 amp  |

CAPABILITY

|                                 |  |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Double wishbone/8.6 in                       |
| Rear Suspension / Wheel Travel  | Double wishbone/9.1 in                       |
| Front Tires                     | 25 x 8-12, radial                            |
| Rear Tires                      | 25 x 10-12, radial                           |
| Steering                        | Electric Power Steering (EPS), Tilt steering |
| Park Brake Type                 | Independent, mechanical disc                 |
| Front Brakes                    | Dual disc, 2-piston caliper                  |

|                              |  |
|------------------------------|--|
| Rear Brakes                  | Dual disc, 1-piston caliper                |
| Ground Clearance             | 10.6 in                                    |
| Fuel Capacity                | 9.5 gal                                    |
| Turning Radius               | 14.0 ft                                    |
| Cargo Bed Dimensions (LxWxH) | 33.4 x 44.1 x 9.1 in                       |
| Cargo Bed Load Capacity      | 699 lb / 600 lb CA Model                   |
| Payload Capacity             | 1,200 lb                                   |
| Seating Capacity             | 2  |
| Towing Capacity              | 1,500 lb                                   |
| Lighting                     | (2) Halogen headlights, (2) LED headlights |

DETAILS

|                     |   |
|---------------------|---|
| Overall Length      | 110.0 in  |
| Overall Width       | 60.0 in   |
| Overall Height      | 75.8 in   |
| Curb Weight         | 1,594.2 lb* / 1,596.4 lb* CA Model  |
| Wheelbase           | 78.9 in   |
| Instruments         | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps |
| Additional Features | Roof, Cast Aluminum Wheels  |
| Color Choices       | Deep Blue   |
| Warranty            | Kawasaki STRONG 3-Year Limited Warranty   |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [peru.kawasaki-la.com](http://peru.kawasaki-la.com) for full product details.