## **TERYX KRX® 1000 TRAIL EDITION**







14.6 x 33.1 x 9.1 in

351 lb

781 lb

N/A



## **POWFR**

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

## DETAILS

Overall Width

Lighting

Cargo Bed

Capacity

Dimensions (LxWxH)

Cargo Bed Load

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

Frame Ladder type, tubular steel

Overall Length 133.3 in

Overall Height 76.6 in

Curb Weight 2,017.6 lb\* / 2,019.8 lb\* CA Model

68.1 in

Wheelbase 98.8 in

Instruments Multi-function digital meter with bar-style tachometer (2

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator

(2) LED headlights, (2) LED taillights, LED stoplight

lamp, EPS warning lamp, and CVT belt warning lamp

Additional Features KQR™ Sport Roof, Front Bumper, Rear Bumper, Nerf Bars,

Steel skid-plates w/ drain holes, WARN® VRX 45 Powersport
Winch

cn

Color Choices Metallic Sierra Blue/Super Black, Metallic Light Gray/Super

Black

Warranty 6 Month Limited Warranty

## **CAPABILITY**

Front Suspension / Wheel Travel Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/18.6 in

Rear Suspension / Wheel Travel 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.2 in (max) / 13.6 in (std)

Fuel Capacity 10.6 gal
Turning Radius 20.3 ft

Scan with camera to view videos, key features and more.

