

2026

VULCAN® 900 CLASSIC LT

Kawasaki

Let the Good Times Roll®



METALLIC GRAPHITE GRAY/METALLIC SPARK BLACK



POWER

|                    |                                                              |
|--------------------|--------------------------------------------------------------|
| Engine             | 4-stroke, 55-degree V-twin, liquid-cooled                    |
| Displacement       | 903cc                                                        |
| Bore x Stroke      | 88.0 x 74.2mm                                                |
| Compression Ratio  | 9.5:1                                                        |
| Maximum Horsepower | 51 hp <sup>1</sup> @ 5,500 rpm                               |
| Maximum Torque     | 58.3 lb-ft @ 3,500 rpm                                       |
| Fuel System        | DFI® with 34mm throttle bodies (2), with sub-throttle valves |
| Ignition           | TCBI with Electronic Advance                                 |
| Transmission       | 5-speed with positive neutral finder                         |
| Final Drive        | Kevlar-reinforced belt                                       |

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| Rear Suspension / Wheel Travel | Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in |
| Front Tire                     | 130/90-16                                                  |
| Rear Tire                      | 180/70-15                                                  |
| Front Brakes                   | Single 300mm hydraulic disc                                |
| Rear Brakes                    | Single 270mm hydraulic disc                                |

DETAILS

|                  |                                             |
|------------------|---------------------------------------------|
| Frame Type       | Semi-double cradle, high-tensile steel      |
| Rake/Trail       | 32° / 6.3 in                                |
| Overall Length   | 97.0 in                                     |
| Overall Width    | 39.6 in                                     |
| Overall Height   | 58.3 in                                     |
| Ground Clearance | 5.3 in                                      |
| Seat Height      | 26.8 in                                     |
| Curb Weight      | 657.1 lb*                                   |
| Fuel Capacity    | 5.3 gal                                     |
| Wheelbase        | 64.8 in                                     |
| Color Choices    | Metallic Graphite Gray/Metallic Spark Black |
| Warranty         | 24 Month Limited Warranty                   |

PERFORMANCE

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Front Suspension / Wheel Travel | 41mm Showa telescopic fork/5.9 in |
|---------------------------------|-----------------------------------|

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [peru.kawasaki-la.com](http://peru.kawasaki-la.com) for full product details.