

2026

# Z900 SE ABS

**Kawasaki**  
Let the Good Times Roll®



METALLIC MATTE GRAPHENESTEEL GRAY/  
METALLIC MATTE CARBON GRAY



## POWER

Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	948cc
Bore x Stroke	73.4 x 56.0mm
Compression Ratio	11.8:1
Maximum Horsepower	123.0 hp <sup>1</sup> @ 9,500 rpm
Maximum Torque	73.1 lb-ft @ 7,700 rpm
Fuel System	DFI® with 36mm throttle bodies
Ignition	TCBI with Electronic Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

## PERFORMANCE

Front Suspension / Wheel Travel	41mm inverted telescopic fork with compression and rebound damping and spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping and spring preload adjustability/5.5 in
Front Tire	120/70-17

Rear Tire	180/55-17
Front Brakes	Dual 300mm semi-floating discs with radial-mount 4-piston Brembo M4.32 monobloc calipers and ABS
Rear Brakes	Single 250mm disc with single-piston caliper and ABS

## DETAILS

Frame Type	Trellis, high tensile steel
Rake/Trail	24.7° / 4.3 in
Overall Length	81.3 in
Overall Width	32.7 in
Overall Height	44.7 in
Ground Clearance	5.7 in
Seat Height	31.9 in
Estimated Dry Weight	427.8 lb** 50-State Model; 425.6 lb** 49-State Model
Curb Weight	471.9 lb* 50-State Model; 469.7 lb* 49-State Model
Fuel Capacity	4.5 gal
Wheelbase	57.1 in
Special Features	5" All-digital TFT color instrumentation, All-LED lighting, USB Type-C outlet, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDELOGY THE APP MOTORCYCLE***
Color Choices	Metallic Matte Graphenesteel Gray/Metallic Matte Carbon Gray
Warranty	12 Month Limited Warranty

Scan with camera  
to view videos,  
key features  
and more.



<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.  
<sup>\*\*</sup>Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
<sup>\*\*\*</sup>RIDELOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.  
<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [peru.kawasaki-la.com](http://peru.kawasaki-la.com) for full product details.