

2026

KLX[®]230R



- LIME GREEN
- BRIGHT WHITE



POWER		Front Brakes	Single 240mm petal disc with a dual-piston caliper
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Rear Brakes	Single 220mm petal disc with single-piston caliper
Displacement	233cc	DETAILS	
Bore x Stroke	67.0 x 66.0mm	Frame Type	High-tensile steel, box-section perimeter
Compression Ratio	9.4:1	Rake/Trail	25.4° / 4.2 in
Fuel System	DFI [®] with 32mm Keihin throttle body	Overall Length	80.5 in
Ignition	TCBI with electronic advance	Overall Width	33.3 in
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Height	47.2 in
Final Drive	Chain	Ground Clearance	11.4 in
PERFORMANCE		Seat Height	35.6 in
Front Suspension / Wheel Travel	37mm telescopic fork/9.8 in	Estimated Dry Weight	247.0 lb** / 249.1 lb** 50-State Model
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/9.8 in	Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
Front Tire	80/100-21	Fuel Capacity	2.0 gal
Rear Tire	100/100-18	Wheelbase	54.1 in
		Color Choices	Lime Green, Bright White
		Warranty	6 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit peru.kawasaki-la.com for full product details.