
## KLX®300SM









Single 300mm petal disc with a dual-piston

Single 240mm petal disc with single-piston

## **POWER**

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

Displacement 292cc

78.0 x 61.2mm

Compression

**Bore x Stroke** 

Ratio

11.1:1

Maximum Horsepower 25.0 hp<sup>1</sup> @ 8,000 rpm

**Maximum Torque** 

17.7 lb-ft @ 7,000 rpm

**Fuel System** 

DFI® with 34mm Keihin throttle body

Ignition

CDI

**Transmission** 

6-speed, return shift with wet multi-disc manual

clutch

Final Drive Chain

## DETAILS

**Rear Tire** 

**Front Brakes** 

**Rear Brakes** 

Frame Type Tubular, semi-double cradle

130/70-17

caliper

caliper

Rake/Trail 25.0°/2.8 in

Overall Length 83.3 in

Overall Width 31.1 in

Overall Height 44.7 in

Ground Clearance 9.3 in

**Seat Height** 

33.9 in

**Estimated Dry** 

Weight

286.6 lb\*\*

Curb Weight 304.3 lb\*

**Fuel Capacity** 

2.0 gal

Wheelbase

56.5 in

**Color Choices** 

Neon Green/Ebony, Battle Gray/Ebony

**Warranty** 12 Month Limited Warranty

## **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted cartridge fork with adjustable compression damping/9.1 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and

spring preload/8.1 in

**Front Tire** 

110/70-17



