

# 2026 KX™ 450

**Kawasaki**  
Let the Good Times Roll®



 LIME GREEN



## POWER

|                              |   |
|------------------------------|---|
| <b>Engine</b>                | 4-stroke, single-cylinder, DOHC, liquid-cooled  |
| <b>Displacement</b>          | 449cc   |
| <b>Bore x Stroke</b>         | 96.0 x 62.1mm   |
| <b>Compression Ratio</b>     | 12.5:1  |
| <b>Fuel System</b>           | DFI® with 44mm Keihin throttle body   |
| <b>Ignition</b>              | Digital CDI with handlebar-controlled power modes                                       |
| <b>Transmission</b>          | 5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation |
| <b>Final Drive</b>           | Chain   |
| <b>Electronic Rider Aids</b> | Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode                      |

|                     |   |
|---------------------|---|
| <b>Front Tire</b>   | 80/100-21   |
| <b>Rear Tire</b>    | 120/80-19   |
| <b>Front Brakes</b> | Single semi-floating 270mm Braking/Sunstar petal disc with Brembo master cylinder and dual-piston caliper |
| <b>Rear Brakes</b>  | Single 240mm Braking/Sunstar petal disc with single-piston caliper  |

## PERFORMANCE

|  |   |
|--|---|
| <b>Front Suspension / Wheel Travel</b> | 49mm Showa inverted telescopic coil-spring fork with 21-way adjustable compression and 22-way adjustable rebound damping/12.0 in  |
| <b>Rear Suspension / Wheel Travel</b>  | Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in |

## DETAILS

|                         |   |
|-------------------------|---|
| <b>Frame Type</b>       | Aluminum perimeter  |
| <b>Rake/Trail</b>       | 26.6° / 4.5 in  |
| <b>Overall Length</b>   | 85.8 in   |
| <b>Overall Width</b>    | 32.3 in   |
| <b>Overall Height</b>   | 50.0 in   |
| <b>Ground Clearance</b> | 13.6 in   |
| <b>Seat Height</b>      | 37.8 in   |
| <b>Curb Weight</b>      | 238.3 lb* without fuel / 248.2 lb*                          |
| <b>Fuel Capacity</b>    | 1.64 gal  |
| <b>Wheelbase</b>        | 58.3 in   |
| <b>Special Features</b> | Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT® |
| <b>Color Choices</b>    | Lime Green  |
| <b>Warranty</b>         | Not Available   |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [peru.kawasaki-la.com](http://peru.kawasaki-la.com) for full product details.