

2026

MULE PRO-FXT™ 1000 LE CAMO

Kawasaki

Let the Good Times Roll®



POWER		DETAILS	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas	Ground Clearance	12.6 in (max), 11.6 in (std)
Displacement	999cc	Fuel Capacity	7.9 gal
Maximum Horsepower	70.0 hp ¹ @ 6,500 rpm	Turning Radius	16.0 ft
Maximum Torque	61.5 lb-ft @ 4,500 rpm	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Bore x Stroke	92.0 x 75.1mm	Cargo Bed Load Capacity	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Compression Ratio	10.1:1	Payload Capacity	1,574.4/1,263.5 lb CA Model
Fuel System	DFI® with 38mm throttle body	Seating Capacity	3-person (1 row), 6 person (2 row)
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Towing Capacity	2,000 lb
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Lighting	(2) Halogen headlights, (2) LED headlights
Engine Braking	Yes		
Alternator Output (max)	90 amp		
CAPABILITY			
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Overall Length	135.8 in
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Overall Width	64.0 in
Front Tires	26 x 9-12, radial	Overall Height	80.9 in
Rear Tires	26 x 11-12, radial	Estimated Dry Weight	1,880.9/1,883.1 lb** CA Model
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering	Curb Weight	1,964.7/1,966.9 lb* CA Model
Park Brake Type	Independent, mechanical disc	Wheelbase	92.3 in
Front Brakes	Dual disc, 2-piston caliper	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Rear Brakes	Dual disc, 1-piston caliper	Wheel Type	Alloy
		Additional Features	Roof, Additional Front Cup Holders
		Color Choices	TRUETIMBER® STRATA