

2026

MULE PRO-MX™ SE

Kawasaki

Let the Good Times Roll®

 GOLD



POWER

| | |
|-------------------------|---|
| Engine | 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled |
| Displacement | 695cc |
| Maximum Horsepower | 44.0 hp ¹ @ 6,000 rpm |
| Maximum Torque | 42.7 lb-ft @ 5,000 rpm |
| Bore x Stroke | 102.0 x 85.0mm |
| Compression Ratio | 10.3:1 |
| Fuel System | DFI® with 44mm throttle body |
| Transmission | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R) |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking | Yes |
| Alternator Output (max) | 35.7 amp |

CAPABILITY

| | |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Double wishbone/8.6 in |
| Rear Suspension / Wheel Travel | Double wishbone/9.1 in |
| Front Tires | 25 x 8-12, radial |
| Rear Tires | 25 x 10-12, radial |
| Steering | Electric Power Steering (EPS), Tilt steering |
| Park Brake Type | Independent, mechanical disc |
| Front Brakes | Dual disc, 2-piston caliper |
| Rear Brakes | Dual disc, 1-piston caliper |

| | |
|------------------------------|--|
| Ground Clearance | 10.6 in |
| Fuel Capacity | 9.5 gal |
| Turning Radius | 14.0 ft |
| Cargo Bed Dimensions (LxWxH) | 33.4 x 44.1 x 9.1 in |
| Cargo Bed Load Capacity | 699 lb / 600 lb CA Model |
| Payload Capacity | 1,200 lb / 1,100 lb CA Model |
| Seating Capacity | 2 |
| Towing Capacity | 1,500 lb |
| Lighting | (2) Halogen headlights, (2) LED headlights |

DETAILS

| | |
|----------------------|---|
| Overall Length | 111.4 in |
| Overall Width | 60.0 in |
| Overall Height | 75.8 in |
| Estimated Dry Weight | 1,550.1 lb** / 1,552.3 lb** CA Model |
| Curb Weight | 1,622.9 lb* / 1,625.1 lb* CA Model |
| Wheelbase | 78.9 in |
| Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps |
| Additional Features | Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels, Painted Body Panels |
| Color Choices | Gold |
| Warranty | Kawasaki STRONG 3-Year Limited Warranty |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit peru.kawasaki-la.com for full product details.