

2026

NINJA® 1100SX SE ABS

Kawasaki

Let the Good Times Roll®



METALLIC DEEP BLUE/METALLIC DIABLO BLACK



POWER		Front Tire	120/70-17
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Rear Tire	190/50-17
Displacement	1,099cc	Front Brakes	Dual 300mm discs with radial-mount 4-piston Brembo M4.32 monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Bore x Stroke	77.0 x 59.0mm	Rear Brakes	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)
Compression Ratio	11.8:1	DETAILS	
Maximum Horsepower	134.0 hp ¹ @ 9,000 rpm		
Maximum Torque	83.2 lb-ft @ 7,600 rpm	Frame Type	Twin-spar aluminum
Fuel System	DFI® with 38mm Electronic Throttle Valves	Rake/Trail	24.0° / 3.9 in
Ignition	TCBI with Digital Advance	Overall Length	82.7 in
Transmission	6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch	Overall Width	31.7 in
Final Drive	Sealed chain	Overall Height	46.9 in / 48.2 in w/ windshield high
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness	Ground Clearance	5.3 in
PERFORMANCE		Seat Height	32.3 in
Front Suspension / Wheel Travel	41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload / 4.7 in	Estimated Dry Weight	469.7 lb**
Rear Suspension / Wheel Travel	Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping, remotely adjustable spring preload / 5.6 in	Curb Weight	516.0 lb*
		Fuel Capacity	5.0 gal
		Wheelbase	56.7 in
		Special Features	4.3" All-digital TFT Instrumentation, All-LED lighting, USB Type-C outlet, Grip heaters, Smartphone Connectivity with available Voice Command via RIDEOLGY THE APP MOTORCYCLE***
		Color Choices	Metallic Deep Blue/Metallic Diablo Black

Scan with camera to view videos, key features and more.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{***}RIDEOLGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit peru.kawasaki-la.com for full product details.