

2026

# VULCAN® S

**Kawasaki**  
Let the Good Times Roll®



-  METALLIC GRAPHITE GRAY/METALLIC SPARK BLACK
-  METALLIC FLAT SPARK BLACK



| POWER                           |                                                                       | Rear Tire            | 160/60-17                                                              |
|---------------------------------|-----------------------------------------------------------------------|----------------------|------------------------------------------------------------------------|
| Engine                          | 4-stroke, 2-cylinder, DOHC, liquid-cooled                             | Front Brakes         | Single 300mm disc with twin-piston caliper (and ABS)                   |
| Displacement                    | 649cc                                                                 | Rear Brakes          | Single 250mm disc with single-piston caliper (and ABS)                 |
| Bore x Stroke                   | 83.0 x 60.0mm                                                         | DETAILS              |                                                                        |
| Compression Ratio               | 10.8:1                                                                | Frame Type           | High-tensile steel diamond frame                                       |
| Maximum Horsepower              | 60 hp <sup>1</sup> @ 7,500 rpm                                        | Rake/Trail           | 31° /4.7 in                                                            |
| Maximum Torque                  | 46.5 lb-ft @ 6,600 rpm                                                | Overall Length       | 90.9 in                                                                |
| Fuel System                     | DFI® with 38mm throttle bodies (2), with sub-throttle valves          | Overall Width        | 34.6 in                                                                |
| Ignition                        | TCBI with Electronic Advance                                          | Overall Height       | 43.3 in                                                                |
| Transmission                    | 6-speed with positive neutral finder                                  | Ground Clearance     | 5.1 in                                                                 |
| Final Drive                     | Sealed chain                                                          | Seat Height          | 27.8 in                                                                |
| Electronic Rider Aids           | Economical Riding Indicator, Anti-lock Brake System (ABS)             | Estimated Dry Weight | 467.5 lb** (ABS), 460.8 lb** (non-ABS)                                 |
| PERFORMANCE                     |                                                                       | Curb Weight          | 498.3 lb* (ABS), 491.7 lb* (non-ABS)                                   |
| Front Suspension / Wheel Travel | 41mm telescopic fork/5.1 in                                           | Fuel Capacity        | 3.7 gal                                                                |
| Rear Suspension / Wheel Travel  | Lay-down offset rear shock with linkage and adjustable preload/3.2 in | Wheelbase            | 62.0 in                                                                |
| Front Tire                      | 120/70-18                                                             | Special Features     | ERGO-FIT®                                                              |
|                                 |                                                                       | Color Choices        | Metallic Graphite Gray/Metallic Spark Black, Metallic Flat Spark Black |
|                                 |                                                                       | Warranty             | 12 Month Limited Warranty                                              |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [peru.kawasaki-la.com](http://peru.kawasaki-la.com) for full product details.