

2027

# KLX®140R L



-  LIME GREEN
-  BRIGHT WHITE



## POWER

|                   |                                                          |
|-------------------|----------------------------------------------------------|
| Engine            | 4-stroke, single-cylinder, SOHC, air-cooled              |
| Displacement      | 144cc                                                    |
| Bore x Stroke     | 58.0 x 54.4mm                                            |
| Compression Ratio | 9.5:1                                                    |
| Fuel System       | Keihin PB20 carburetor                                   |
| Ignition          | Digital DC-CDI                                           |
| Transmission      | 5-speed, return shift, with wet multi-disc manual clutch |
| Final Drive       | Chain                                                    |

## PERFORMANCE

|                                 |                                                                                                                                |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 33mm telescopic fork/7.1 in                                                                                                    |
| Rear Suspension / Wheel Travel  | Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in |
| Front Tire                      | 70/100-19                                                                                                                      |
| Rear Tire                       | 90/100-16                                                                                                                      |

|              |                                                    |
|--------------|----------------------------------------------------|
| Front Brakes | Single 220mm petal disc with a dual-piston caliper |
| Rear Brakes  | Single 186mm petal disc with single-piston caliper |

## DETAILS

|                      |                                           |
|----------------------|-------------------------------------------|
| Frame Type           | High-tensile steel, box-section perimeter |
| Rake/Trail           | 27.0° / 3.8 in                            |
| Overall Length       | 74.6 in                                   |
| Overall Width        | 31.1 in                                   |
| Overall Height       | 42.3 in                                   |
| Ground Clearance     | 10.0 in                                   |
| Seat Height          | 31.5 in                                   |
| Estimated Dry Weight | 196.2 lb**                                |
| Curb Weight          | 209.4 lb*                                 |
| Fuel Capacity        | 1.5 gal                                   |
| Wheelbase            | 50.6 in                                   |
| Color Choices        | Lime Green, Bright White                  |
| Warranty             | 6 Month Limited Warranty                  |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [peru.kawasaki-la.com](http://peru.kawasaki-la.com) for full product details.