NEW 2027

# KLX®300SM ABS

Kawasaki
Let the Good Times Roll®

NEON GREEN/EBONY

BATTLE GRAY/EBONY

## POWER

| | |
|---|---|
| **Engine** | 4-stroke, single-cylinder, DOHC, liquid-cooled |
| **Displacement** | 292cc |
| **Bore x Stroke** | 78.0 x 61.2mm |
| **Compression Ratio** | 10.9:1 |
| **Maximum Horsepower** | 26.8 hp[1] @ 8,000 rpm |
| **Maximum Torque** | 18.4 lb-ft @ 6,800 rpm |
| **Fuel System** | DFI® with 34mm Keihin throttle body |
| **Ignition** | CDI |
| **Transmission** | 6-speed, return shift with wet multi-disc manual clutch |
| **Final Drive** | Chain |
| **Electronic Rider Aids** | Anti-lock Brake System (ABS) |

## PERFORMANCE

| | |
|---|---|
| **Front Suspension / Wheel Travel** | 43mm inverted telescopic fork with adjustable compression damping/9.1 in |
| **Rear Suspension / Wheel Travel** | Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/8.1 in |
| **Front Tire** | 110/70-17 |
| **Rear Tire** | 130/70-17 |
| **Front Brakes** | Single 300mm petal disc with a dual-piston caliper and ABS |
| **Rear Brakes** | Single 240mm petal disc with single-piston caliper |

## DETAILS

| | |
|---|---|
| **Frame Type** | Tubular, semi-double cradle |
| **Rake/Trail** | 25.0° /2.8 in |
| **Overall Length** | 83.1 in |
| **Overall Width** | 30.7 in |
| **Overall Height** | 44.7 in |
| **Ground Clearance** | 9.4 in |
| **Seat Height** | 33.9 in |
| **Estimated Dry Weight** | 288.9 lb** |
| **Curb Weight** | 306.5 lb* |
| **Fuel Capacity** | 2.0 gal |
| **Wheelbase** | 56.3 in |
| **Special Features** | LCD instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP MOTORCYCLE |
| **Color Choices** | Neon Green/Ebony, Battle Gray/Ebony |
| **Warranty** | 12 Month Limited Warranty |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit peru.kawasaki-la.com for full product details.