2027

# VULCAN® S ABS

Kawasaki
Let the Good Times Roll®

METALLIC CARBON GRAY/METALLIC BLUISH GREEN

METALLIC FLAT SPARK BLACK

## POWER

| | |
|---|---|
| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled |
| Displacement | 649cc |
| Bore x Stroke | 83.0 x 60.0mm |
| Compression Ratio | 10.8:1 |
| Maximum Horsepower | 60 hp[1] @ 7,500 rpm |
| Maximum Torque | 46.5 lb-ft @ 6,600 rpm |
| Fuel System | DFI® with 38mm throttle bodies (2), with sub-throttle valves |
| Ignition | TCBI with Electronic Advance |
| Transmission | 6-speed with positive neutral finder |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Economical Riding Indicator, Anti-lock Brake System (ABS) |

## PERFORMANCE

| | |
|---|---|
| Front Suspension / Wheel Travel | 41mm telescopic fork/5.1 in |
| Rear Suspension / Wheel Travel | Lay-down offset rear shock with linkage and adjustable preload/3.2 in |
| Front Tire | 120/70-18 |
| Rear Tire | 160/60-17 |
| Front Brakes | Single 300mm disc with 2-piston caliper and ABS |
| Rear Brakes | Single 250mm disc with single-piston caliper and ABS |

## DETAILS

| | |
|---|---|
| Frame Type | High-tensile steel diamond frame |
| Rake/Trail | 31° /4.7 in |
| Overall Length | 90.9 in |
| Overall Width | 34.6 in |
| Overall Height | 43.3 in |
| Ground Clearance | 5.1 in |
| Seat Height | 27.8 in |
| Estimated Dry Weight | 467.5 lb** (ABS), 460.8 lb** (non-ABS) |
| Curb Weight | 498.3 lb* (ABS), 491.7 lb* (non-ABS) |
| Fuel Capacity | 3.7 gal |
| Wheelbase | 62.0 in |
| Special Features | ERGO-FIT® |
| Color Choices | Metallic Carbon Gray/Metallic Bluish Green, Metallic Flat Spark Black |
| Warranty | 12 Month Limited Warranty |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit peru.kawasaki-la.com for full product details.