ACTUALIZADA 2027

NINJA® 650 ABS

Kawasaki
Let the Good Times Roll®

- VERDE LIME
- NEGRO METALLIC FLAT SPARK/GRIS METALLIC CARBON
- AZUL METALLIC MATTE TWILIGHT/ROJO CANDY PERSIMMON
- PLATA GALAXY

POTENCIA

Motor	4-stroke, Parallel Twin, DOHC, liquid-cooled
Cilindrada	649cc
Diámetro por carrera	83.0 x 60.0mm
Relación de compresión	10.8:1
Potencia máxima	67.0 hp[1] @ 8,000 rpm
Par motor máximo	48.5 lb-ft @ 6,700 rpm
Sistema de combustible	DFI® with dual 36mm Keihin throttle bodies
Encendido	TCBI with Electronic Advance
Transmisión	6-speed
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Kawasaki Quick Shifter (KQS) available as an accessory

RENDIMIENTO

Suspensión delantera/recorrido del neumático	37mm inverted Showa Separate Function Big Piston Fork (SFF-BP)/4.9 in
Suspensión trasera/recorrido del neumático	Horizontal back-link with adjustable spring preload/5.1 in
Neumático delantero	120/70 x 17
Neumático trasero	160/60 x 17
Frenos delanteros	Dual semi-floating 300mm discs with radial-mounted 4-piston calipers and ABS
Frenos traseros	Single 220mm disc with single-piston caliper and ABS

DETALLES

Tipo de chasis	Trellis, high-tensile steel
Ángulo de dirección/Avance	24.0° /3.9 in
Largo total	80.5 in
Ancho total	29.1 in
Altura del asiento	44.9 in
Distancia al suelo	4.9 in
Altura del asiento	30.9 in
Peso seco estimado	394.7 lb** 50-State Model; 392.5 lb** 49-State Model
Peso en orden de marcha	427.8 lb* 50-State Model; 425.6 lb* 49-State Model
Depósito de combustible	4.0 gal
Distancia entre ejes	54.9 in
Características especiales	4.3-in all-digital TFT color instrumentation, Smartphone Connectivity with available Voice Command via RIDEOLOGY THE APP MOTORCYCLE***
Colores disponibles	Lime Green, Metallic Flat Spark Black/Metallic Carbon Gray, Metallic Matte Twilight Blue/Candy Persimmon Red, Galaxy Silver
Garantía	Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave y más.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
***RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visite peru.kawasaki-la.com para obtener detalles completos del producto.